

applying a torque in a tightening direction a first of the tightened threaded fasteners until a break away torque is reached;

measuring the torque values applied to the first tightened fastener and measuring the angle through which the first fastener rotates;

defining a first zero-angle point to be a point at which a tangent from a torque versus angle plot, created from the measured torque and angle values from the first tightened fastener, crosses an angle axis;

defining a first audit angle to be the angle between the first zero-angle point and the angle associated break away torque for the first tightened threaded fastener;

applying a torque in a tightening direction a second of the tightened threaded fasteners until a break away torque is reached;

measuring the torque values applied to the second tightened fastener and measuring the angle through which the second fastener rotates;

defining a second zero angle point to be a point at which a tangent from a torque versus angle plot, created from the measured torque and angle values from the second tightened fastener, crosses an angle axis;

defining a second audit angle to be the angle between the second zero angle point and the angle associated break away torque for the second tightened threaded fastener; and

comparing the first and second audit angles to determine relative clamp loads.

19. (New) A method as in claim 18 wherein the torque is applied until an angle of rotation between 1 and 15 degrees is achieved.

20. (New) A method as in claim 18 wherein audit angles are defined for the remainder of the plurality of tightened threaded fasteners and the plurality of audit angles are compared.

B1

21. (New) A method as in claims 18 wherein the first and second audit angles are compared to a predetermined audit angle.

---

In the drawings:

In Fig.1 and Fig. 2 please amend the drawings to indicate prior art as indicated in red. In Fig. 2 please change the term Eleastic to Elastic to correct the misspelling as indicated in red.